

blueplanet 155 + 165 TL3

String inverters for utility-scale solar power plants
up to multi-megawatt solar parks.



Pushing the limits.

Superior efficiencies and
overload capacity through silicon
carbide technology

Outstanding power density for
easy logistics and installation

Decentralised design or ‚Virtual
Central‘ concept possible

Overvoltage protection AC/
DC and for communication
interfaces available

Lean commissioning and updates
via remote services



Technical Data

| DC input data | 155 TL3 | 165 TL3 |
|---|--|--|
| Max. recommended PV generator power | 232 500 W | 247 500 W |
| MPP range | 875 – 1 300 V | 960 – 1 300 V |
| Operating range | 875 – 1 450 V | 960 – 1 450 V |
| Rated DC voltage / start voltage | 900 V / 1 000 V | 1000 V / 1 100 V |
| Max. no-load voltage | 1 500 V | 1 500 V |
| Max. input current | 183 A | 183 A |
| Max. short circuit current $I_{sc,max}$ | 300 A | 300 A |
| Number of MPP tracker | 1 | 1 |
| Connection per tracker | 1 - 2 | 1 - 2 |
| AC output data | | |
| Rated output | 155 000 VA | 165 000 VA |
| Max. power | 155 000 VA | 165 000 VA |
| Line voltage | 600 V (3P+PE) | 660 V (3P+PE) |
| Voltage range (Ph-Ph) | 480 – 690 V | 480 – 760 V |
| Rated frequency (range) | 50 Hz / 60 Hz (45 – 65 Hz) | 50 Hz / 60 Hz (45 – 65 Hz) |
| Rated current | 3 x 149.5 A | 3 x 144.5 A |
| Max. current | 3 x 152.0 A | 3 x 152.0 A |
| Reactive power / cos phi | | 0 – 100 % Snom / 0,30 ind. – 0,30 cap. |
| Max. total harmonic distortion (THD) | ≤ 3 % | ≤ 3 % |
| Number of grid phases | 3 | 3 |
| General data | | |
| Max. efficiency | 99.1 % | 99.1 % |
| Europ. efficiency | 98.9 % | 99.0 % |
| CEC efficiency | 98.9 % | 99.0 % |
| Standby consumption | < 10 W | < 10 W |
| Circuitry topology | transformerless | transformerless |
| Mechanical data | | |
| Display | LEDs | LEDs |
| Control units | webserver, supports mobile devices | webserver, supports mobile devices |
| Interfaces | Ethernet (Modbus TCP, Sunspec), RS485 (KACO-protocol), USB, optional: 4-DI | |
| Fault signalling relay | potential-free NOC max. 30 V / 1 A | potential-free NOC max. 30 V / 1 A |
| DC connection | cable lug, max. 240 mm ² (0.372 in ²) Cu or Al | |
| AC connection | cable lug, max. 240 mm ² (0.372 in ²) Cu or Al | |
| Ambient temperature | -25 °C – +60 °C ¹⁾ | -25 °C – +60 °C ¹⁾ |
| Humidity | 0 – 100 % | 0 – 100 % |
| Max. installation elevation (above MSL) | 3 000 m | 3 000 m |
| Min. distance from coast | 500 m | 500 m |
| Cooling | temperature controlled fan | temperature controlled fan |
| Protection class | IP66 / NEMA 4X | IP66 / NEMA 4X |
| Noise emission | 59.2 db (A) | 59.2 db (A) |
| H x W x D | 719 x 699 x 460 mm | 719 x 699 x 460 mm |
| Weight | 78.2 kg | 78.2 kg |
| Certifications | | |
| Safety | IEC 62109-1/-2, EN 61000-6-1/-2/-4, EN 61000-3-11/-12, EN 55011 group 1, class A EN 62920 Emission class A / Immunity class A UL62109-1, UL1741, CSA-C22.2 No.107.1, CSA-C22.2 No.62109-1, CSA-C22.2 No.62109-2 | |
| Grid connection rule | overview see homepage / download area | |

¹⁾ Power derating at high ambient temperatures

| Versions | S | XL |
|------------------------|------------|------------|
| Number of DC inputs | 1 - 2 | 1 - 2 |
| DC switch | - | ✓ |
| DC SPD | Type 1 + 2 | Type 1 + 2 |
| AC SPD | ○ | ○ |
| RS485 interface SPD | ○ | ○ |
| Ethernet interface SPD | ○ | ○ |
| PID Set | ○ | ○ |

standard = ✓ upgradeable = ○

The text and figures reflect the current technical state at the time of printing. Subject to technical changes. Errors and omissions excepted. This current version replaces all older versions. Download the most current version at: www.kaco-newenergy.com